

Tap Water Reverse Osmosis system LPRO series



LPRO-B series (Basic design)



LPRO-P series (Premier design)

LPRO-B16 series reverse osmosis systems are designed and manufactured for commercial and light industrial applications. These systems have been engineered for capacities ranging from 1,200-9,000 gallons per day for low TDS feed water design (Feed water TDS < 1,500).

Applications

- Drinking water
- Food & Beverage
- Electroplating
- Power plant
- Preparation of medicine
- Petrochemical industry
- Eyeglass
- Waste water reuse
- Metallurgy
- Pretreatment of EDI or Mixed Bed

Standard Features

■ Control system

- Relay and timer control
- Timer adjustable
- Tank level control
- Low pressure/High pressure protection
- Auto flush
- Pretreatment lockout control backup

■ Membrane element and pressure vessel

- Membrane model---LP21-4040
- Membrane manufacturer---Vontron/DOW/Hydronautics/Others
- Membrane rejection---99%-99.6%
- Pressure vessel spec.---FRP, 300PSI, end port
- Pressure vessel manufacturer---ROPV/Wave Cyber/First Line/Others

■ Cartridge Filtration

- Housing---4.5''*20''
- Filter cartridge---4.5''*20'', 5micron
- Quantity--- 1 pc

■ Boost Pump

- Type---Vertical multistage centrifugal
- Pump material---SS304/SS316/Carbon steel
- Connection---DIN flange
- Brand---CNP

■ Documentation Included

- Operation and maintenance manual
- Drawings: P&ID, Electrical diagram

■ Benefits

- Fully equipped and customizable
- Expandable and skid mounted
- Components easily accessible
- Pre-plumbed wired and assembled
- Individually tested and preserved
- Low operation and maintenance costs
- Easy maintenance and servicing
- 1-Year limited warranty

■ Options and Upgrades

- PLC controller
- SS304 seamless pressure vessel
- Anti-scalant dosing system
- Clean-in-place (CIP) system
- Pre-treatment system
- PH meter
- Feed water conductivity meter
- Grundfos pump

Ordering Guide

Order Example	LPRO-B16	9000	TB	220S60
Type				
Nominal Capacity (GPD)				
Connection (code)				
Power supply (code)				

Connection Port	Code
Thread, BSPT	TB
Thread, NPT	TN

Power Supply	Code
220VAC / 50hz / single phase	220S50
230VAC / 50hz / single phase	230S50
240VAC / 50hz / single phase	240S50
100VAC / 60hz / single phase	100S50
110VAC / 60hz / single phase	110S50
120VAC / 60hz / single phase	120S60
127VAC / 60hz / single phase	127S60
200VAC / 60hz / single phase	200S60
220VAC / 60hz / single phase	220S60
240VAC / 60hz / single phase	240S60
380VAC / 50hz / three phase	380T50
400VAC / 50hz / three phase	400T50
415VAC / 50hz / three phase	415T50
440VAC / 50hz / three phase	440T50
200VAC / 60hz / three phase	200T60
208VAC / 60hz / three phase	208T60
220VAC / 60hz / three phase	220T60
240VAC / 60hz / three phase	240T60
380VAC / 60hz / three phase	380T60
440VAC / 60hz / three phase	440T60
460VAC / 60hz / three phase	460T60
480VAC / 60hz / three phase	480T60

Specifications

MODEL	LPRO-B16-1500	LPRO-B16-3000	LPRO-B16-4500	LPRO-B16-6000	LPRO-B16-9000
Feed Water TDS ¹	<1500ppm	<1500ppm	<1500ppm	<1500ppm	<1500ppm
Nominal Perm. rate ²	0.25m ³ /hr	0.5m ³ /hr	0.75m ³ /hr	1.0m ³ /hr	1.5m ³ /hr
Approx. Conc. rate	0.12m ³ /hr	0.25m ³ /hr	0.3m ³ /hr	0.4m ³ /hr	0.6m ³ /hr
Approx. conc. recycle rate	1.1m ³ /hr	0.8m ³ /hr	0.8m ³ /hr	0.6m ³ /hr	0.6m ³ /hr
Approx. Feed rate	0.38m ³ /hr	0.7m ³ /hr	1.0m ³ /hr	1.5m ³ /hr	2.2m ³ /hr
Recovery Rate	50~75%	50~75%	60~75%	60~75%	60~75%
Pump and Motor					
Manufacturer	CNP	CNP	CNP	CNP	CNP
Model	CDLF2-9 (60hz)	CDLF2-9 (60hz)	CDLF2-9 (60hz)	CDLF2-9 (60hz)	CDLF2-11 (60hz)
Motor HP	2.2kw	2.2kw	2.2kw	2.2kw	2.2kw
Wet contact Material	SS304	SS304	SS304	SS304	SS304
Design flow rate ³	1.48m ³ /hr	1.5m ³ /hr	1.8m ³ /hr	2.1m ³ /hr	2.8m ³ /hr
Pump pressure	11.1bar	11.1bar	10.7bar	10.3bar	10.8bar
Membranes Elements and Housings					
Membranes quantity	1	2	3	4	6
Memb. housing Qty	1 (single element)	2 (single element)	3 (single element)	4 (single element)	6 (single element)
Membrane housing array	1	1→1	1→1→1	1→1→1→1	1→1→1→1→1→1
Valves					
Auto inlet valve	3/4" SS304; solenoid	3/4" SS304; solenoid	1" SS304; solenoid	1" SS304; solenoid	1" SS304; solenoid
Auto flush valve	1/2" SS304; solenoid	1/2" SS304; solenoid	1/2" SS304; solenoid	1/2" SS304; solenoid	1/2" SS304; solenoid
Feed valve after HP pump	3/4" SS304;adjustable	3/4" SS304;adjustable	3/4" SS304;adjustable	3/4" SS304;adjustable	1" SS304;adjustable
Concentrate valve	1/2" SS304;adjustable	1/2" SS304;adjustable	1/2" SS304;adjustable	1/2" SS304;adjustable	1/2" SS304;adjustable
Recycle valve	1/2" SS304;adjustable	1/2" SS304;adjustable	1/2" SS304;adjustable	1/2" SS304;adjustable	1/2" SS304;adjustable
Recycle check valve	1/2" UPVC	1/2" UPVC	1/2" UPVC	1/2" UPVC	1/2" UPVC
Manual CIP inlet	3/4" UPVC ball valve	3/4" UPVC ball valve	3/4" UPVC ball valve	3/4" UPVC ball valve	3/4" UPVC ball valve
Installation					
Inlet	1"BSPT or NPT	1"BSPT or NPT	1"BSPT or NPT	1"BSPT or NPT	1"BSPT or NPT
Permeate	1"BSPT or NPT	1"BSPT or NPT	1"BSPT or NPT	1"BSPT or NPT	1"BSPT or NPT
Drain	1/2"BSPT or NPT	1/2"BSPT or NPT	1/2"BSPT or NPT	1/2"BSPT or NPT	1/2"BSPT or NPT
CIP inlet	3/4"BSPT or NPT	3/4"BSPT or NPT	3/4"BSPT or NPT	3/4"BSPT or NPT	3/4"BSPT or NPT
CIP outlet	3/4"BSPT or NPT	3/4"BSPT or NPT	3/4"BSPT or NPT	3/4"BSPT or NPT	3/4"BSPT or NPT
Package Dimension					
Approx. Height	1650mm	1650mm	1650mm	1650mm	1650mm
Approx. Width	700mm	700mm	700mm	700mm	700mm
Approx. Depth	650mm	650mm	650mm	800mm	800mm
Approx. Shipping Weight	180kg	190kg	200kg	215kg	235kg
Options					
Antiscalant Feed System	Metering pump: 1.5 L/hr Chemical tank: 60-100L	Metering pump: 1.5 L/hr Chemical tank: 60-100L	Metering pump: 1.5 L/hr Chemical tank: 60-100L	Metering pump: 1.5 L/hr Chemical tank: 60-100L	Metering pump: 1.5 L/hr Chemical tank: 60-100L
CIP system	CIP tank: 200L CIPpump: 2m ³ /h@3bar CIP filter: 4.5"×20"BB	CIP tank: 200L CIPpump: 2m ³ /h@3bar CIP filter: 4.5"×20"BB	CIP tank: 200L CIPpump: 2m ³ /h@3bar CIP filter: 4.5"×20"BB	CIP tank: 200L CIPpump: 2m ³ /h@3bar CIP filter: 4.5"×20"BB	CIP tank: 200L CIPpump: 2m ³ /h@3bar CIP filter: 4.5"×20"BB
Pretreatment: PTSC836 series	PTSC836-10	PTSC836-10	PTSC836-12	PTSC836-14	PTSC836-16
Pretreatment: PTSCS836 series	PTSCS836-10	PTSCS836-10	PTSCS836-12	PTSCS836-14	PTSCS836-16